



CHARACTERIZING NATURAL ATTENUATION OF BHC IN SEASONALLY FLUCTUATING GROUNDWATER

¹A. Davis, ¹G.G. Fennemore, ¹S.O. Helgen, and ²K.A. Hoenke

¹Geomega, 2995 Baseline Road, Suite 202, Boulder, CO 80303; Phone: (303)442-2549; Fax: (303)938-8123.

²Chevron Environmental Management Company, 6001 Bollinger Canyon Road, San Ramon, CA 94583; Phone: (925)842-9259; Fax: (925)842-0213.

ABSTRACT

Though commercially produced BHC (lindane) may be reagent grade γ -BHC, it often consists of α -BHC (60-70%), β -BHC (5-12%), and γ -BHC (10-15%), δ -BHC (6-10%) that are each regulated at very low (ng/l) concentrations. Evaluation of natural attenuation for each isomer, following a removal action to meet regulatory standards in groundwater at an Orlando, Florida, site, was confounded by water table oscillations (± 1.5 m) that were inversely correlated with groundwater BHC concentrations (i.e., higher water table = lower BHC concentrations). However, when BHCs were evaluated on a total mass basis, a clear decline (10% per year) over seven years was apparent ($r^2 = 0.84$) following first-order kinetics. Over this period, the plume center of mass did not migrate in the direction of groundwater flow, remaining within 30 m of its nexus, compared to contemporaneous rapid transit across the site of an MTBE plume originating upgradient. Because of water-level-induced variability in measurement of individual groundwater BHC isomer concentrations, a total BHC, rather than individual isomer metric, would seem to be an appropriate approach to evaluate the efficacy of natural attenuation and regulatory compliance.

Key words: natural attenuation, water table oscillations, regulatory standards