


CHE 670 Sustainability Seminar

GHG Calculators

David A. Carter
Kansas State University Pollution Prevention Institute

January 6, 2010





“I think you should be more explicit here in step two...”

EPA Greenhouse Gas Equivalencies Calculator

- Uses the Emissions & Generation Resource Integrated Database (eGRID) U.S. annual non-baseload CO₂ output emission rate
- Puts carbon dioxide (CO₂) emissions reductions in everyday terms
- May be useful in communicating your greenhouse gas reduction strategy, reduction targets, or other initiatives aimed at reducing greenhouse gas emissions
- Useful for emissions **reductions** from energy efficiency or renewable energy programs
- Only for CO₂, no other GHG
- <http://www.epa.gov/RDEE/energy-resources/calculator.html>

EPA's Pollution Prevention GHG Calculator

- Quantifies reductions based on conversion factors
 - Electricity conservation
 - Green energy
 - Fuel substitution
 - Greening chemistry
 - Water conservation
 - Materials management
- GHG Conversion Tool May 2009.xls

EPA's Mandatory Reporting Rule

- Tier 1: $\text{CO}_2 = 1 \times 10^{-3} \times \text{Fuel} \times \text{HHV} \times \text{EF}$
 - Fuel = mass or volume of fuel combusted/year (mass in short tons, volume in scf [gas] or gallons [liquid])
 - HHV = default high heat value (Table C-1) (mmBTU/mass or volume)
 - EF = fuel-specific default CO₂ emission factor
 - 1×10^{-3} = conversion factor for kg to metric tons

EPA's Mandatory Reporting Rule

- Tier 2: $CO_2 = 1 \times 10^{-3} \times \text{Fuel} \times \text{HHV} \times \text{EF}$
 - HHV = annual average high heat value of fuel from all valid samples for the year
 - If fuel samples > monthly, $\text{HHV (annual)} = \frac{\sum (\text{HHV})_i \times (\text{Fuel})_i}{\sum (\text{Fuel})_i}$
- Tier 3: depends on solid, liquid, gas
- Tier 4: CEMS

EPA Applicability Tool

- Assess whether your facility would be required to report GHG
- Applicability depends on the source categories and, for some source categories, the emission level or production capacity
- Not intended for **Suppliers** of fossil fuels or industrial GHGs and **Engine Manufacturers**
- **Applicability Tool**

The Climate Registry

- General Reporting Protocol, May 2008
- Electric Power Sector Protocol
- Oil and Gas Production Protocol
- Local Government Operations Protocol (adopted June 2, 2009)
- Data Quality Tiers
 - A1 Direct Monitoring
 - A2 Calculation based on fuel use (measured carbon content and measured heat content)
 - B Calculation based on fuel use (measured heat content and default carbon content, or vice versa)
 - C Calculation based on fuel use (default CO₂ emission factors by fuel type)

EPA Climate Leaders Simplified GHG Emissions Calculator (SGEC)

- Based on Climate Leaders GHG protocol guidance
- Determines direct and indirect emissions at all sources in the company
- http://www.epa.gov/climateleaders/documents/sgec_tool_v2%208.xls

GHG Protocol

- Default emission factors are averages based on the most extensive data sets available
- Largely identical to those used by the Intergovernmental Panel on Climate Change (IPCC)
- Businesses should use custom values whenever possible
- Cross-sector tools
 - Stationary combustion
 - Purchased electricity, heat, and steam
 - Transport or mobile sources
 - Employee commuting
 - Refrigeration and air-conditioning
- <http://www.ghgprotocol.org/calculation-tools/all-tools>
 - Stationary combustion tool

American College & University Presidents Climate Commitment (ACUPCC)

- Clean Air-Cool Planet Campus Carbon Calculator: <http://www.cleanair-coolplanet.org/toolkit/content/view/43/124/>

Comparison of Calculators

57,200,000 scf natural gas

- GHG Equivalencies – 2,860 metric tons CO₂e (therms)
- P2 GHG Calculator – 3,128 (scf); 3,043 (therms)
- Climate Leaders – 3,131 (scf)
- EPA Applicability Tool – 3,118 (scf)
- GHG Protocol – 3,053 (scf); 3,386 (therms)
- ACUPCC – 3,017 (MMBTU)